

Specification for Contamination Control Mat

Part-FSTEP30

- An economical solution to contamination control
- Manufactured from anti- microbial agent
- Protects against the growth of organisms such as bacteria, mould and milde.
- Adhesive coated surface captures dirt and dust particles
- Traps dirt from wheels and pedestrian foot traffic.
- Disposable layer- peel off soiled sheets to reveal layer.
- Adhesive backed pads stick directly to floor surface
- Approved for direct food contact.



Material: Peel of film sheets – Produced from a proprietary blend of polyolefin resins. Each pad contains 30 layers of film, yet has a profile less than 3mm.

Pull tabs- manufactured from polyester film and numbered consecutively ensuring removal of one layer at a time.

Adhesive – Acrylic contacting a nontoxic antimicrobial additive that provides protection against the growth of organisms including bacteria, mould and mildew.

Approved by the US FDA for food direct contact (21 CFR 175.105)

Surface finish – Smooth

Product Height – 10mm nominal

Operating temperature – 0 - 60°C

Environmental Resistance – Dry, indoor environments.

Typical Applications: Many industrial applications including entrances to clean room environments, entrances to offices from shop floors, food applications and hospitals.

Installation method –Supplied with self-adhesive backing that adheres to most floor surfaces.

- Product Performance – Fatigue: ●
- Slip Resistance●
- Wear: ●
- Low / High ● ●●●→

Dimensions	Weight	Packaging Dimensions	Packaging Qty	Colour
460 x 1143mm (18 x 45")	5KG	48 x 3 x 118cm	4	White Grey Blue

Contents		Standard	Test Result
Dimensions	a. Thickness (mm/layer) b. Width c. Length	0.050 (+or – 0.005mm) (+or-5mm) (+or-5mm)	0.050mm
Adhesion (g/25mm)	a. Mat Layer b. Floor Layer	220 (+or-30g) 700 (+or-30g)	220 GRS 690 GRS
Tensile Strength (Kg/10mm)		➤ 1.2	1.4
Elongation (%)		➤ 250%	270%
Ability if dust removal (five steps with weight 100kg)			99.90%
Heat Proof Reistance		70°C + or -3°C/48 HRS	Suitable
Cold Proof Resistance		-13°C +or -3°C/48 HRS	Suitable
Weather Condition Resistance		200 HRS	Suitable
Application		Suitable	Suitable
(External) Appearance	a. Colour b. Contamination c. Pin Hole d. Air Bubble e. Brokage	Suitable	Suitable

The information contained within this spec sheet is for guidance only. We make no warranties expressed or implied and assume no liability regarding any use of this information. (Re-view Nov 16)