



### **The AUTOPA Plain Round Bollard (Stainless) 129mm - 204mm**

The AUTOPA range of Plain Round Stainless Steel Bollards offer an elegant means to establish control of parking and access. Plain Round Stainless Steel Bollards are ideal for use around pedestrian precincts, shops, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

The complete range of Plain Round Stainless Steel Bollards is available in diameters from 60mm to 204mm and is available in Grade 304 or Grade 316 Stainless Steel.

Plain Round Stainless Steel Bollards are also available in Removable versions.

### **Product Range**

<b>Order Code</b>	<b>Description</b>	<b>Weight</b>
138 125 129	129mm (Ragged)	9.4kg
138 125 130	129mm (Flanged)	7.3kg
138 125 139	139mm (Ragged)	10.0kg
138 125 154	154mm (Ragged)	11.3kg
138 125 153	154mm (Flanged)	9.4kg
138 125 168	168mm (Ragged)	12.5kg
138 125 173	168mm (Flanged)	10.2kg
138 125 204	204mm (Ragged)	15.0kg
138 125 206	204mm (Flanged)	12.3kg

### **Product details**

1,000mm Tall.

Flanged for bolting down or Ragged for casting in.

Grade 304 Stainless steel finish. Grade 316 also available.

### **Installation & use**

It is recommended that bollards are placed no further than 1,200mm apart to ensure no vehicle may pass between the bollards.

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm cube) by means of four M12 bolts.

Ragged bollards require an excavated hole of approximately 400mm cube for installation.

This product is guaranteed for 12 months (*if installed and used correctly*).