

# Speedy Tower



## Common Dimensions

Aluminium stiles diameter (mm)	40mm
Rungs diameter (mm)	35mm
Distance between rungs (mm)	250mm
Wheels diameter (mm)	125mm
Base length w/o stabilisers (mm)	1,760mm
Base width w/o stabilisers (mm)	830mm
Hatch size (mm)	0,540 x 0,570m

## Product Dimensions

PRODUCT SKU	PLATFORM HEIGHT (M)	APPROX WORKING HEIGHT (M)	OVERALL HEIGHT (M)	FRAME WIDTH (M)	FRAME DEPTH (M)	BASE LENGTH INC STABILISERS (M)	BASE WIDTH INC STABILISERS (M)	WEIGHT (NETT KG)
3010-030	1,0	2,6	1,9	1,8	0,8			26.0
3010-031	1,8	3,4	2,9	1,8	0,8			9.5
3010-032	3,5	5,1	4,6	1,8	0,8	3,8	3,1	28.7
3010-033	5,2	6,8	6,3	1,8	0,8	3,8	3,1	20.5t

The Speedy Tower is tough, efficient and versatile thanks to its foldable base and spun-rung ‘Duraclimb’ technology. The Speedy tower provides a strong but lightweight option designed for regular use with no tools required - simply slot and lock into place. The folding base unit is easy to manoeuvre around on four lockable castors, or fold in half to fit through narrow doorways. The addition of guardrail and extension packs allow the system to be used on projects up to 7 metres.

- » Quick and easy erection – no tools required
- » Manufactured from 40mm ‘duraclimb’ tube for regular use
- » Flexible modular design to reach different heights
- » Four lockable castors
- » Anti-slip 1.78 x 0.78m platform
- » Stabilisers included above 3.5m platform heights

Notice:

Pack 1 is the base pack. Simply add additional packs to gain extra working height in the following order:

Pack 1 + 2 gives an approximate working height of 3.4m

Pack 1 + 2 + 3 gives an approximate working height of 5.1m

Pack 1 + 2 + 3 + 4 gives an approximate working height of 6.8m

## Standards & Classification

- » Max Safe Working Load 200kg
- » EN1004

## Warranty

- » 3 Year

## Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (M)	SHIPPING WIDTH (MM)	SHIPPING HEIGHT (MM)	SHIPPING VOLUME (M <sup>3</sup> )	SHIPPING WEIGHT (GROSS KG)	BARCODE
3010-030	1,9	770	500	0,739	27.5	3178740036881
3010-031	1,8	770	800	0,110	10.7	3178740036898
3010-032	1,8	770	300	0,422	29	3178740036904
3010-033	1,8	770	250	0,352	20.6	3178740036911