



**THE RIGHT BALANCE**  
Speed, Performance, Value

**Warrior**<sup>®</sup> Washdown Scale  
pg. 10

# Contents

<b>Raven</b> ® Price Computing Retail Scales 	3
<b>WBZ</b> Washdown Retail Scales	4
<b>AZextra</b> Price-Computing Retail Scales	5
<b>Astro</b> ® Compact Scales 	6
<b>LBK</b> Weighing Scales	7
<b>WBW</b> Washdown Scales	8
<b>CBK</b> Bench Checkweighing Scales	9
<b>Warrior</b> ® Washdown Scales	10
<b>CPWplus</b> Weighing Scales	11
<b>GBK</b> Bench Checkweighing Scales	12
<b>GFK</b> Floor Checkweighing Scales	13
<b>CCEU</b> and <b>CCSA Coin Counting</b> Scales	14
<b>Dune</b> ® Portable Compact Balances	15

## Features



Tare



Backlit Display



Internal Rechargeable Battery



Battery Operated



RS-232 Output



Multiple Weighing Units



External Calibration



Date



Time



IP66 Rated



CE Type Approved



NMI Approved (Canada)



NRCS Approved (South America)

## To place an order

United Kingdom

Merlin Industrial Products Ltd

Unit A43 Kingsley Close,

Lee Mill Industrial Estate

Ivybridge

Devon

PL21 9LL

United Kingdom

Call: 0845 124 9955

Fax: 0845 125 9955

[info@merlin-industrial.co.uk](mailto:info@merlin-industrial.co.uk)

# Raven® Price Computing Retail Scales

Only available from UK, Germany, and South Africa offices



Simple to use, Raven price computing scales offer 40 PLU memories that can be accessed directly from the keypad for quick recall of products. The backlit display clearly show both the operator and customer the weight, unit price and total price. A built-in battery makes the Raven ideal for market traders and applications needing complete portability.

## Features

- Backlit LCD shows weight, unit price and total price, to provide the key information simultaneously
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Heavy-duty rubber feet ensure stability of unit
- Overload protection helps prevent damage to internal components
- Solid ABS housing is durable for industrial uses
- Rechargeable battery included for operation almost anywhere
- Auto power-off to save energy
- Built-in memory for storing 40 products (PLU's)



Rear View

Model	RAV 3D	RAV 6D	RAV 15D	RAV 30D
<b>Capacity</b>	1.5kg / 3kg	3kg / 6kg	6kg / 15kg	15kg / 30kg
<b>Readability</b>	0.5g / 1g	1g / 2g	2g / 5g	5g / 10g
<b>Tare Range</b>	Full range			
<b>Pan Size</b>	220x310mm			
<b>Weighing Units</b>	kg			
<b>Calibration</b>	External calibration			
<b>Display</b>	Backlit LCD with 18mm-high digits			
<b>Power Supply</b>	12VDC 50/60Hz 1A adapter / Internal rechargeable battery			
<b>PLU Memories</b>	20 keys, 40 PLU			
<b>Operating Temperature</b>	-10° to 40°C			
<b>Overall Dim.</b>	330x335x115mm (wxdxh)			
<b>Approvals</b>	EC type approval			



## Accessories

Item number	Description
• 303149761	Fish Scoop (complete with fitting to scale)
• 303149759	Vegetable Scoop (complete with fitting to scale)
• 303149760	Confectionery Scoop (complete with fitting to scale)
• 700660290	Calibration certificate

## Applications

- Weighing
- Price computing

# WBZ Washdown Retail Scales



A smart choice for delis, restaurants, coffee shops and bakeries that sell food based on weight, the WBZ washdown retail scale simplifies price computing. Weight, price per unit and total cost are displayed for both operator and customer on WBZ's backlit dual LCD. With a large grade 304 stainless steel pan and streamlined design, the WBZ is easy to clean and fits neatly on crowded counters or smaller prep tables. The WBZ is approved for selling by weight and carries an IP66 rating, so it is protected against water and flour dust.

## Features

- Backlit LCD shows weight, unit price and total price, to provide the key information simultaneously
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows easy cleaning
- Level indicator and adjustable feet ensure proper balance setup for optimum weighing results
- IP66-rated for protection against water and dust
- Preset tare function speeds the process of repetitive weighing
- Price displayed in choice of available currencies
- Auto-clear function enables the last item to be reset each time the scale returns to zero

## Applications

- Weighing
- Price computing

Model	WBZ 3	WBZ 6	WBZ 15
Capacity	3kg	6kg	15kg
Readability	1g	2g	5g
Tare Range	Full range		
Pan Size	210x173mm		
Weighing Units	kg		
Calibration	External calibration		
Display	Backlit LCD with 16mm-high digits		
Power Supply	12VDC 50/60Hz 800mA adapter / Internal rechargeable battery		
Operating Temperature	-10° to 40°C		
Overall Dim.	231x265x153mm (wxdxh)		
Approvals	EC type approval: T7476    NRCS approved: SA1460		

## Accessories

Item number	Description
• 303200002	In-use cover (pack of 10)
• 303200003	In-use cover (pack of 20)
• 303209190	In-use cover
• 303147960	Small scoop (complete with fitting to scale)
• 303147961	Medium scoop (complete with fitting to scale)
• 303147959	Large scoop (complete with fitting to scale)
• 700660290	Calibration certificate



# AZextra Price-Computing Retail Scales



The AZextra retail scale offers weighing and price computing functions needed for meat counters, shops and markets. The AZextra comes with internal memory capable of storing up to 103 product look-ups. A selectable auto-clear function enables the last item to be reset each time the scale returns to zero. Time, date, weight, unit price and total cost transmit easily to printers via RS-232 interface. The AZ extra is approved for use in trade.

## Features

- Backlit LCD shows weight, unit price and total price, to provide the key information simultaneously
- Pillar display standard on P versions
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows easy cleaning
- Product Look Up (PLU) memory locations store a range of items for recall as needed
- Price displayed in choice of available currencies
- Rechargeable battery included for operation almost anywhere
- Switchable between price per kg and price per 100g
- Auto-clear function enables the last item to be reset each time the scale returns to zero
- Optional RS-232 interface is available to provide speedy connection to computers and printers

## Applications

- Weighing
- Price computing

Model	AZextra 3	AZextra 6	AZextra 15	AZextra 30	AZextra 3P	AZextra 6P	AZextra 15P	AZextra 30P
<b>Capacity</b>	3kg	6kg	15kg	30kg	3kg	6kg	15kg	30kg
<b>Readability</b>	1g	2g	5g	10g	1g	2g	5g	10g
<b>Tare Range</b>	Full range							
<b>Pan Size</b>	225x275mm							
<b>Weighing Units</b>	kg							
<b>Calibration</b>	External calibration							
<b>Display</b>	Backlit LCD with 20mm-high digits							
<b>Power Supply</b>	Mains power cord / Internal rechargeable battery							
<b>PLU Memories</b>	103							
<b>Operating Temperature</b>	-10° to 40°C							
<b>Overall Dim.</b>	315x355x110mm (wxdxh)				315x355x535mm (wxdxh)			
<b>Approvals</b>	EC type approval: T7068		NRCS approved: SA1422			NMI approval: 6/4D/335		

## Accessories

- | Item number  | Description  |
|--------------|--|
| • 3074010266 | RS-232 cable (null-modem)  |
| • 3074010507 | RS-232 to USB adapter<br>(must order corresponding RS-232 cable) |
| • 303149761  | Fish Scoop (complete with fitting to scale)                      |
| • 303149759  | Vegetable Scoop (complete with fitting to scale)                 |
| • 303149760  | Confectionery Scoop (complete with fitting to scale)             |
| • 600002028  | Adam DU data collection program                                  |
| • 700660290  | Calibration certificate  |



## Accessories

- | Item number | Description               |
|-------------|---------------------------|
| • 700200056 | In-use cover              |
| • 700200063 | In-use cover (pack of 5)  |
| • 700200064 | In-use cover (pack of 10) |



Astro portioning scales provide accurate measurements for the food service industry. The Astro's durable stainless steel construction can easily be wiped down. A large LCD displays results in green during normal weighing. If the scale is overloaded or is not set on a level surface, readings will be displayed in red, clearly notifying the user that they are not receiving precise results.

## Features

- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows easy cleaning
- Overload protection helps prevent damage to internal components
- Rugged stainless steel housing for ultimate durability
- Operates with AC adapter (included) or batteries (not included)

## Applications

- Weighing

Model	ASC 2001	ASC 4000	ASC 8000
Capacity	2000g	4000g	8000g
Readability	0.1g	0.5g	1g
Tare Range	Full range		
Pan Size	160x180mm		
Weighing Units	g, kg, lb, lb:oz, oz		
Calibration	External calibration		
Display	LCD with 18mm-high digits		
Power Supply	6VDC 500mA adapter / 2 x AAA batteries		
Operating Temperature	0° to 40°C		
Overall Dim.	212x167x66mm (wxdxh)		



# LBK Weighing Scales



With easy operation and a sleek, compact profile, LBK is ideal for food service and production areas. Food preparation tasks are simplified with the LBK, including ingredient measurement, portioning, sample weighing, dietary control, and food processing activities. The LBK features a large, easy-to-clean stainless steel pan to accommodate different bowl sizes, making it an excellent choice for delicatessens, restaurants, cafes and pizza parlours. The sealed keypad and ABS plastic housing allow speedy clean-up of spills. LBK scales are well-suited for repetitive tasks, as the most frequently used keys are colour-coded for fast recognition.

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Large, grade 304 stainless steel pan allows easy cleaning
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Level indicator and adjustable feet ensure proper balance setup for optimum weighing results
- Splash-proof housing, keypad and display mean easy cleaning
- Lightweight design simplifies transport and portability
- Rechargeable battery included for operation almost anywhere

## Applications

- Weighing
- Parts counting
- Percentage weighing

Model	LBK 3	LBK 6	LBK 12	LBK 30
<b>Capacity</b>	3kg	6kg	12kg	30kg
<b>Readability</b>	0.5g	1g	2g	5g
<b>Tare Range</b>	Full range			
<b>Pan Size</b>	250x180mm			
<b>Weighing Units</b>	g, kg, lb, lb:oz, oz			
<b>Calibration</b>	External calibration			
<b>Display</b>	Backlit LCD with 24mm-high digits			
<b>Power Supply</b>	Mains power cord / Internal rechargeable battery			
<b>Operating Temperature</b>	0° to 40°C			
<b>Overall Dim.</b>	250x307x110mm (wxdxh)			

## Accessories

Item number	Description
• 302205006	In-use cover
• 700200057	In-use cover (pack of 5)
• 700200058	In-use cover (pack of 10)
• 1120011156	ATP thermal printer
• 3126011263	ATP thermal printer paper
• 3126011281	ATP thermal printer paper (pack of 10)
• 700660290	Calibration certificate



# WBW Washdown Scales



The WBW washdown scale is ideal for weighing bulk recipe ingredients or measuring individual servings in restaurants, bakeries, cafes and kitchens. The scale is easily wiped down in compliance with sanitation requirements, and its IP66 rating means the WBW is sealed to protect against flour dust or moisture. A capacity tracker monitors weight when making batches or adding ingredients. With a compact design, the WBW fits comfortably on a bench or countertop.

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Capacity tracker built into display for easily monitoring possible overloads
- Optional rear display doubles equipment placement possibilities for easy viewing
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Heavy-duty rubber feet ensure stability of unit
- IP66-rated for protection against water and dust
- Checkweighing LEDs light to clearly show under, over and acceptable limits
- Large, grade 304 stainless steel pan allows easy cleaning
- Sealed keypad protects against dirt and spills

## Applications

- Weighing
- Checkweighing

Model	WBW 2	WBW 4	WBW 8	WBW 16	WBW 3M	WBW 6M	WBW 15M
<b>Capacity</b>	2kg	4kg	8kg	16kg	3kg	6kg	15kg
<b>Readability</b>	0.2g	0.5g	1g	2g	1g	2g	5g
<b>Tare Range</b>	Full range						
<b>Pan Size</b>	210x173mm						
<b>Weighing Units</b>	g, kg, lb, lb:oz						
<b>Calibration</b>	External calibration						
<b>Display</b>	Backlit LCD with 20mm-high digits						
<b>Power Supply</b>	12VDC 50/60Hz 800mA adapter / Internal rechargeable battery						
<b>Operating Temperature</b>	-10° to 40°C						
<b>Overall Dim.</b>	231x265x153mm (wxdxh)						
<b>Approvals</b>	N/A				EC type, NRCS, and NMI approved		

## Accessories

Item number	Description
• 2020010755	Rear Display (factory fitted)
• 303200002	In-use cover (pack of 10)
• 303200003	In-use cover (pack of 20)
• 303209190	In-use cover
• 303147960	Small scoop (complete with fitting to scale)
• 303147961	Medium scoop (complete with fitting to scale)
• 303147959	Large scoop (complete with fitting to scale)
• 700660290	Calibration certificate



# CBK Bench Checkweighing Scales



The sleek design and smooth, easy-to-clean contours of the versatile CBK bench checkweighing scale bring unmatched value to food service operations. Features and functions such as percentage weighing, checkweighing, and memory accumulation facilitate ingredient measurement and the weighing of food in take-out containers. A capacity tracker is built directly into the display, making it simple to monitor portions. The CBK offers a vivid, backlit LCD that is easily visible in any lighting conditions, so it is well-suited for kitchens or prep settings.

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Capacity tracker built into display for easily monitoring possible overloads
- Checkweighing LEDs light to clearly show under, over and acceptable limits
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows easy cleaning
- Rugged construction stands up to industrial use
- Optional RS-232 interface is available to provide speedy connection to computers and printers
- Optional USB interface simplifies data communication
- Rechargeable battery included for operation almost anywhere
- Quick and easy configuration using the keypad
- Memory accumulation totals results
- Checkweighing with audible alarm

## Applications

- Weighing
- Parts counting
- Percentage weighing
- Checkweighing
- Accumulation of weight

Model	CBK 4	CBK 8	CBK 8H	CBK 16	CBK 32	CBK 48	CBK 3M	CBK 6M	CBK 15M	CBK 30M
<b>Capacity</b>	4kg	8kg	8kg	16kg	32kg	48kg	3kg	6kg	15kg	30kg
<b>Readability</b>	0.1g	0.2g	0.1g	0.5g	1g	2g	1g	2g	5g	10g
<b>Tare Range</b>	Full range									
<b>Pan Size</b>	225x275mm									
<b>Weighing Units</b>	g, kg, lb, lb:oz, oz						g, kg			
<b>Calibration</b>	External calibration									
<b>Display</b>	Backlit LCD with 20mm-high digits									
<b>Power Supply</b>	Mains power cord / Internal rechargeable battery									
<b>Operating Temperature</b>	0° to 40°C									
<b>Overall Dim.</b>	315x355x110mm (wxdxh)									
<b>Approvals</b>	N/A						EC type approved			

## Accessories

Item number	Description
• 302000001	Hard carrying case with lock
• 302205006	In-use cover
• 700200057	In-use cover (pack of 5)
• 700200058	In-use cover (pack of 10)
• 1120011156	ATP thermal printer
• 3126011263	ATP thermal printer paper
• 3126011281	ATP thermal printer paper (pack of 10)



## Accessories

Item number	Description
• 3074010266	RS-232 cable (null-modem)
• 3074010507	RS-232 to USB adapter (must order corresponding RS-232 cable)
• 600002028	Adam DU data collection program
• 202000001	Weigh-below hook (factory-fitted)
• 700660290	Calibration certificate

# Warrior® Washdown Scales



WSK

WBK

WFK

Rugged durability makes the Warrior a winner for measuring large quantities in demanding food industry environments. With an IP66 rating, the Warrior's internal components are protected against flour dust and moisture, while the grade 304 stainless steel base cleans easily during batching tasks. Dynamic weighing capability allows the Warrior to accurately measure liquids, and easy-to-read, coloured LED indicators facilitate repetitive checkweighing of samples

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Capacity tracker built into display for easily monitoring possible overloads
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows easy cleaning
- Rugged stainless steel construction for ultimate durability
- Checkweighing LEDs light to clearly show under, over and acceptable limits
- Rechargeable battery included for operation almost anywhere
- IP66-rated for protection against water and dust

## Applications

- Weighing
- Percentage weighing
- Dynamic / animal weighing
- Parts counting
- Checkweighing

Model	WSK 8	WSK 16	WSK 32	WBK 32	WBK 32H	WBK 75	WFK 75	WFK 75H	WFK 150	WLK 150
<b>Capacity</b>	8kg	16kg	32kg	32kg	32kg	75kg	75kg	75kg	150kg	150kg
<b>Readability</b>	0.5g	1g	2g	2g	1g	5g	5g	1g	10g	10g
<b>Tare Range</b>	Full range									
<b>Pan Size</b>	250x250mm			300x400mm			400x500mm		450x600mm	
<b>Weighing Units</b>	g, kg, lb, lb:oz, oz, N									
<b>Calibration</b>	External calibration									
<b>Display</b>	Backlit LCD with 40mm-high digits									
<b>Power Supply</b>	12VDC 50/60Hz 800mA adapter / Internal rechargeable battery									
<b>Operating Temperature</b>	-10° to 40°C									
<b>Overall Dim.</b> (wxdxh)	250x345x532mm			300x500x587mm			400x590x972mm		450x700x972mm	

## Accessories

- | Item number  | Description                            |
|--------------|--|
| • 3102311619 | In-use cover                           |
| • 1120011156 | ATP thermal printer                    |
| • 3126011263 | ATP thermal printer paper              |
| • 3126011281 | ATP thermal printer paper (pack of 10) |
| • 3104012889 | RS-232 cable (factory fitted)          |
| • 1100011297 | AE402 relay box                        |
| • 600002028  | Adam DU data collection program        |
| • 700660290  | Calibration certificate                |



# CPWplus Weighing Scales



Top to Bottom: CPWplus, CPWplus M, CPWplus L

With its many platform and power options, the CPWplus bench and floor scale provides exceptional value and durability to meet the demands of food processing applications. CPWplus is simple to operate and offers a stainless steel platform that is easy to clean after weighing food ingredients. The hold function facilitates dynamic weighing of liquids. The CPWplus indicator can be set up and positioned anywhere for easy viewing. Ideal for measuring ingredients in restaurants, weighing dough in pizza parlors, or mixing batches in food factories.

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Remote display can be placed anywhere near the base unit for convenient viewing
- Large, grade 304 stainless steel pan allows easy cleaning
- Optional RS-232 interface is available to provide speedy connection to computers and printers
- Auto power-off to save energy
- Hold function freezes the displayed weight, allowing time to lapse without losing the result
- Scratch-resistant aluminum housing protects internal components
- Wall-mount bracket for placing indicator on vertical surface
- Simple operation allows quick startup and use with little or no training

Model	CPWplus 6	CPWplus 15	CPWplus 35	CPWplus 75	CPWplus 150	CPWplus 200	
Model M			CPWplus 35M	CPWplus 75M	CPWplus 150M	CPWplus 200M	
Model L			CPWplus 35L	CPWplus 75L	CPWplus 150L	CPWplus 200L	CPWplus 300L
<b>Capacity</b>	6kg	15kg	35kg	75kg	150kg	200kg	300kg
<b>Readability</b>	0.002kg	0.005kg	0.01kg	0.02kg	0.05kg	0.05kg	0.1kg
<b>Tare Range</b>	Full range						
<b>Pan Size</b>			300x300x50mm	M - 500x500mm	L - 900x600mm		
<b>Weighing Units</b>	kg, lb, lb:oz, oz						
<b>Calibration</b>	External calibration						
<b>Display</b>	Backlit LCD with 22mm-high digits						
<b>Power Supply</b>	300x300x50mm = 12VDC 50/60Hz 150mA adapter / 6 x AA batteries M & L versions = 12VDC 50/60Hz 500mA adapter / Internal rechargeable battery						
<b>Oper. Temp.</b>	0° to 40°C						
<b>Overall Dim.</b>	300x300x50mm		M - 500x500x78mm (wxdxh)		L - 900x600x78mm (wxdxh)		

## Accessories

### Item number

- 700100099 Hard carrying case with lock (300 x 300mm pan size only)
- 1120011156 ATP thermal printer
- 3126011263 ATP thermal printer paper
- 3126011281 ATP thermal printer paper (pack of 10)
- 700200059 Non-slip rubber mat (CPWplus L only)
- 3074010266 RS-232 cable (null-modem)
- 3074010507 RS-232 to USB adapter (must order corresponding RS-232 cable)
- 600002028 Adam DU data collection program
- 700660290 Calibration certificate

### Description



## Applications

- Weighing
- Display hold

# GBK Bench Checkweighing Scales



The GBK bench checkweighing scale offers durability and value for batching in commercial food applications. Functions on the GBK include dynamic weighing to measure liquid ingredients, checkweighing to monitor the final product and automatic accumulation to provide totals for weight readings. The GBK features a sturdy, grade 304 stainless steel pan that removes easily for frequent cleaning during batching tasks, while a sealed keypad protects against accidental spills. The adjustable indicator rotates and angles to provide the ideal viewing position.

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Checkweighing LEDs light to clearly show under, over and acceptable limits
- Capacity tracker built into display for easily monitoring possible overloads
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows easy cleaning
- Rugged construction stands up to industrial use
- Optional RS-232 interface is available to provide speedy connection to computers and printers
- Rechargeable battery included for operation almost anywhere
- Checkweighing with audible alarm
- Memory accumulation totals results
- Quick and easy configuration using the keypad

## Applications

- Weighing
- Percentage weighing
- Dynamic / animal weighing
- Parts counting
- Checkweighing
- Accumulation of weight

Model	GBK 8	GBK 16	GBK 32	GBK 60	GBK 120	GBK 6M	GBK 15M	GBK 30M	GBK 60M	GBK 150M
<b>Capacity</b>	8kg	16kg	32kg	60kg	120kg	6kg	15kg	30kg	60kg	150kg
<b>Readability</b>	0.1g	0.5g	1g	2g	5g	2g	5g	10g	20g	50g
<b>Tare Range</b>	Full range									
<b>Pan Size</b>	300x400mm									
<b>Weighing Units</b>	g, kg					kg				
<b>Calibration</b>	External calibration									
<b>Display</b>	Backlit LCD with 20mm-high digits									
<b>Power Supply</b>	Mains power cord / Internal rechargeable battery									
<b>Operating Temperature</b>	-10° to 40°C									
<b>Overall Dim.</b>	300x520x680mm (wxdxh)									
<b>Approvals</b>	(M models only) EC type approval: UK2860 NMI approval: 6/9C/309 NRCS approved: SA1464									



## Accessories

Item number	Description
• 3052010526	In-use cover
• 1120011156	ATP thermal printer
• 3126011263	ATP thermal printer paper
• 3126011281	ATP thermal printer paper (pack of 10)

## Accessories

Item number	Description
• 3074010266	RS-232 cable (null-modem)
• 3074010507	RS-232 to USB adapter (must order corresponding RS-232 cable)
• 600002028	Adam DU data collection program
• 700660290	Calibration certificate

# GFK Floor Checkweighing Scales



With its high capacities and large, grade 304 stainless steel platform, the GFK floor checkweighing scale is ideal for bigger batching applications and high-volume food production tasks. Features such as capacity tracker and automatic memory accumulation help tackle larger food-weighing operations such as catering and special events. Checkweighing is simplified with the GFK, as coloured LEDs show if samples are within a specified range. The indicator can be used with or without the pillar, offering flexibility when reading results. The GFK-M is approved for use in trade.

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Capacity tracker built into display for easily monitoring possible overloads
- Checkweighing LEDs light to clearly show under, over and acceptable limits
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Large, grade 304 stainless steel pan allows easy cleaning
- Rugged construction stands up to industrial use
- Solid ABS housing is durable for industrial uses
- Splash-proof housing, keypad and display mean easy cleaning
- Optional RS-232 interface is available to provide speedy connection to computers and printers
- Rechargeable battery included for operation almost anywhere
- Checkweighing with audible alarm

## Applications

- Weighing
- Percentage weighing
- Dynamic / animal weighing
- Parts counting
- Checkweighing
- Checkcounting

Model	GFK 75	GFK 75H	GFK 150	GFK 150H	GFK 300	GFK 600	GFK 60M	GFK 150M	GFK 300M
<b>Capacity</b>	75kg	75kg	150kg	150kg	300kg	600kg	60kg	150kg	300kg
<b>Readability</b>	5g	1g	10g	2g	20g	50g	20g	50g	100g
<b>Tare Range</b>	Full range								
<b>Pan Size</b>	400x500mm / GFK600=600x800mm								
<b>Weighing Units</b>	g, kg						kg		
<b>Calibration</b>	External calibration								
<b>Display</b>	Backlit LCD with 20mm-high digits								
<b>Power Supply</b>	Mains power cord / Internal rechargeable battery								
<b>Operating Temperature</b>	-10° to 40°C								
<b>Overall Dim.</b>	400x620x860mm (wxdxh) / GFK600=600x940x900mm (wxdxh)								
<b>Approvals</b>	(M models only) EC type approval: UK2860 NMI approval: 6/9C/309 NRCS approved: SA1464								



## Accessories

- | Item number  | Description                            |
|--------------|--|
| • 3052010526 | In-use cover                           |
| • 1120011156 | ATP thermal printer                    |
| • 3126011263 | ATP thermal printer paper              |
| • 3126011281 | ATP thermal printer paper (pack of 10) |
| • 3074010266 | RS-232 cable (null-modem)              |

## Accessories

- | Item number  | Description   |
|--------------|---|
| • 3074010507 | RS-232 to USB adapter (must order corresponding RS-232 cable) |
| • 600002028  | Adam DU data collection program                               |
| • 700660288  | Calibration certificate (IHS, LHS, AFK 600, GFK 600, PTM)     |
| • 700660290  | Calibration certificate                                       |

# CCEU & CCSA Coin Counting Scales

CCEU only available from UK, and Germany offices  
 CCSA only available from the South Africa office



The CCEU and CCSA coin and token counting scales are designed to handle large numbers of coins in retail applications, providing accurate counts for nine different coins and three token values. It includes a rechargeable battery, so it operates smoothly when power is unavailable. A memory accumulation function keeps track of amount totals, displaying the figures on a vivid, backlit LCD that is readily visible in any lighting conditions. The durable stainless steel platform is easy to clean, while its large size accommodates a variety of container sizes. Colour-coded keys speeds up operation. Security is of the utmost importance when counting currency, because of this, these models provides password control to eliminate unauthorised use of the scale. Speedy communication is achieved so tabulations can be printed or saved.

## Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Level indicator and adjustable feet ensure proper balance setup for optimum weighing results
- Rechargeable battery included for operation almost anywhere
- Security password control
- Memory accumulation totals coin values
- Accommodates nine different coin units and two different token sizes
- CCEU counts Euros or sterling coins, but can be configured for other currencies as well
- CCSA counts South African Rands or sterling coins, but can be configured for other currencies as well

## Applications

- Coin counting
- Weighing

Model	CCEU 20	CCSA 20
Capacity	20kg	20kg
Readability	1g	1g
Tare Range	Full range	
Pan Size	225x275mm	
Weighing Units	kg, PCS	
Calibration	External calibration	
Display	Backlit LCD with 20mm-high digits	
Power Supply	Mains power cord / Internal rechargeable battery	
Operating Temperature	-10° to 40°C	
Overall Dim.	315x355x110mm (wxdxh)	

## Accessories

Item number	Description
• 302000001	Hard carrying case with lock
• 302205006	In-use cover
• 700200057	In-use cover (pack of 5)
• 700200058	In-use cover (pack of 10)
• 1120011156	ATP thermal printer
• 3126011263	ATP thermal printer paper
• 3126011281	ATP thermal printer paper (pack of 10)



## Accessories

Item number	Description
• 3074010266	RS-232 cable (null-modem)
• 3074010507	RS-232 to USB adapter (must order corresponding RS-232 cable)
• 700660290	Calibration certificate

# Dune® Portable Compact Balances



The Dune offers a fast, convenient way to measure recipe ingredients or to perform portion control tasks in food service operations. The Dune is powered by battery or an AC adapter, which is included with the balance. This means the Dune can be transported between kitchens and serving areas, or used in a production line where electricity is unavailable. The large plastic pan removes easily for cleaning and readily accommodates food items or small food containers, which can be tared out with the touch of a button. The Dune's simplicity and portability make it ideal for most culinary settings.

## Features

- High-contrast display is easily visible from a distance
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Solid, one-piece construction is lightweight and easy to clean
- Auto power-off to save energy
- Low-battery indicator alerts users when batteries need replacement
- Operates with AC adapter (included) or batteries (not included)
- External calibration allows for verification and adjustment with weights

## Applications

- Weighing

Model	DCT 201	DCT 2000	DCT 5000
Capacity	200g	2000g	5000g
Readability	0.1g	1g	2g
Tare Range	Full range		
Pan Size	145x145mm		
Weighing Units	g, oz	g, lb, oz	
Calibration	External calibration		
Display	LCD with 15mm-high digits		
Power Supply	12VAC 50/60Hz 150mA adapter / 6 x AA batteries		
Operating Temperature	0° to 40°C		
Overall Dim.	147x208x40mm (wxdxh)		

## Accessories

- | Item number | Description             | Price |
|-------------|-------------------------|-------|
| • 700660290 | Calibration certificate |       |

