

# All Terrain Mobile Safety Steps



## Common Dimensions

Top Platform W x D	560 x 405
Tread Width	560
Tread Depth	180

## Product Dimensions

PRODUCT SKU PUNCHED	PRODUCT SKU ANTI-SLIP	APPROX. WORKING HEIGHT	PLATFORM HEIGHT	TREAD COUNT	OVERALL HEIGHT	OVERALL WIDTH	OVERALL DEPTH	WEIGHT (NETT KG)
2021-004	2022-004	2,600	1,000	4	2,000	800	990	35.0
2021-005	2022-005	2,850	1,250	5	2,250	800	1,130	40.0
2021-006	2022-006	3,100	1,500	6	2,500	800	1,280	45.0
2021-007	2022-007	3,350	1,750	7	2,750	800	1,420	50.0
2021-008	2022-008	3,600	2,000	8	3,000	800	1,570	55.0

## Technical Description

Easy to fold and open mobile safety step with large platform fitted with toe boards and intermediate guardrails for safety.

- » Semi-pneumatic wheels make it easy to manoeuvre on uneven surfaces
- » Deep top platform
- » Rubber pads on front legs help keep ladder in place when in use
- » Solid perforated tread provides excellent slip resistance and drainage
- » Scratch resistant powder coated finish
- » Designed to conform to EN 131-7

## Standards & Classification

- » Maximum Working Load 150kg
- » Conforms to BS EN 131-7 & Kite Marked

## Warranty

- » 1 Year

## Shipping Dimensions

PRODUCT SKU PUNCHED	PRODUCT SKU ANTI-SLIP	SHIPPING LENGTH (HEIGHT)	SHIPPING WIDTH	SHIPPING DEPTH	SHIPPING VOLUME (M <sup>3</sup> )	SHIPPING WEIGHT (GROSS KG)	BARCODE PUNCHED	BARCODE ANTI-SLIP
2021-004	2022-004	2,000	800	990	1.5840	35.0	5060169481435	5060169481480
2021-005	2022-005	2,250	800	1,130	2.0340	40.0	5060169481442	5060169481497
2021-006	2022-006	2,500	800	1,280	2.5600	45.0	5060169481459	5060169481503
2021-007	2022-007	1,420	800	2,750	3.1240	50.0	5060169481466	5060169481510
2021-008	2022-008	1,570	800	3,000	3.7680	55.0	5060169481473	5060169481527



Supplied By  
 Merlin Industrial Products LTD  
 Kingsley Close, East Way  
 Lee Mill Industrial Estate  
 Ivybridge  
 Devon  
 PL21 9LL  
 United Kingdom

[www.merlin-industrial.co.uk](http://www.merlin-industrial.co.uk)  
[sales@merlin-industrial.co.uk](mailto:sales@merlin-industrial.co.uk)

Call: 0845 124 9955  
 Fax: 0845 125 9955

## Notes

All dimensions stated in mm unless marked otherwise. Engineering tolerance +/- 10% or 10mm, whichever is greater. Where applicable, approximate working height is calculated as 1,600mm + Last Climbing Height (4th rung from the ladder top) or the Platform Height.