

Series 60AS - Grey statically conductive polyurethane tyred wheels in zinc and stainless steel castors

- Electrically conductive grey non-marking thermoplastic polyurethane tyred wheel (Shore 90-A).
- Ball bearing bore.
- Bearings supplied with 2RS waterproof protection as standard.
- Quiet, easy running.
- Scratch and tear resistant.
- Suitable for internal and external use. Eg: concrete, ceramic tiles, asphalt etc.
- Not suitable for rough terrain.
- Suitable for use where alcohol, hydrocarbons, solvents and weak acids are present.
- Suitable in a wet environment.
- Not recommended for use with strong bases.
- Operating temperature -20°C to +70°C
- Wheels have an electrical resistance of less than 104Ω in accordance with ISO 2882.

Ball Bearing Wheel



								ball bearing
80	25	8	30	100	0.15	60AS0001		
80	32	8	36	130	0.18	60AS0011		
100	25	8	30	120	0.22	60AS0002		
100	32	8	36	150	0.25	60AS0012		
125	25	8	30	130	0.31	60AS0003		
125	32	8	36	160	0.33	60AS0013		
150	32	12	32	180	0.52	60AS0014		
200	32	12	32	180	1.07	60AS0016		
200	50	20	50	500	1.21	60AS0026		

Other wheel sizes available on request.

Zinc plated castors



80	25	105	100x80	80x60	12	100	0.70	60AS3011	0.51	60AS3001	0.89	60AS3021	0.55	60AS3031	0.89	60AS3041	
100	25	128	100x80	80x60	12	120	0.84	60AS3012	0.65	60AS3002	1.03	60AS3022	0.68	60AS3032	1.03	60AS3042	
125	25	155	100x80	80x60	12	130	1.21	60AS3013	1.73	60AS3003	1.33	60AS3023	0.96	60AS3033	1.33	60AS3043	

Stainless steel castors



80	25	105	100x80	80x60	12	100	0.70	60AS3061	0.51	60AS3051	0.89	60AS3071	0.55	60AS3081	0.89	60AS3091	
100	25	128	100x80	80x60	12	120	0.84	60AS3062	0.65	60AS3052	1.03	60AS3072	0.68	60AS3082	1.03	60AS3092	
125	25	155	100x80	80x60	12	130	1.21	60AS3063	1.73	60AS3053	1.33	60AS3073	0.96	60AS3083	1.33	60AS3093	

Supplied by Merlin Industrial Products Ltd - 0845 124 9955 - Email sales@merlin-industrial.co.uk