

LOW LEVEL SERIES

Zinc Plated Pressed Steel Construction
Double Ball Race Swivel Head



Top Plate Fixing



96 Shore A
Orange Polyurethane
On Steel

-20°C to +80°C

Dia (mm)	Height (mm)	Plate (mm)	Centres (mm)	Fixing Bolt (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)
35	65	60 x 48	48 x 35	6			BZXH35PTBJ	100	27	33

Loose Stem Fixing



96 Shore A
Orange Polyurethane
On Steel

-20°C to +80°C

Dia (mm)	Height (mm)	Stem (mm)	Head Dia (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)
35	58	10	46			BZXH35PTBJST10	100	17	31

LOW LEVEL SERIES

Zinc Plated Pressed Steel Construction
Double Ball Race Swivel Head



PLATE FIXING



75-200kg



40-50mm

Top Plate Fixing

Dia (mm)	Height (mm)	Plate (mm)	Centres (mm)	Fixing Bolt (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)	Material	Temp Range
50	73	95 x 67	76 x 44	8			BZH632X50NY	75	14 x 2	44	Nylon	-20°C to +80°C
50	73	95 x 67	76 x 44	8			2BZXL50NY	90	15 x 2	48	Nylon	-20°C to +80°C

Top Plate Fixing

Dia (mm)	Height (mm)	Plate (mm)	Centres (mm)	Fixing Bolt (mm)	Type	Bearing	Code	Load (kg)	Tread (mm)	Radius (mm)	Material	Temp Range
40	64	65 x 65	50 x 50	6			-	-	-	-	Black Nylon	-30°C to +80°C
50	75	65 x 65	50 x 50	6			BZXH50NY	200	28	50	White Nylon	-30°C to +80°C
							BZXH50NYBR	200	28	50	White Nylon	-30°C to +80°C
							BZXHF50NY	200	28	-	White Nylon	-30°C to +80°C